

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

- 1           1.       (Currently amended) A method for performing a lock-free update  
2       to one or more fields in an existing node in a linked list, comprising:  
3           receiving a reference to the existing node in the linked list, wherein the  
4       existing node contains the one or more fields to be updated;  
5           obtaining a new node to be added to the linked list, wherein other  
6       processes do not possess references to the new node and therefore cannot initially  
7       access the new node;  
8           copying a snapshot of the existing node to the new node, which includes  
9       copying a next pointer of the existing node to the new node, so that the new node  
10      points to a node immediately following the existing node;  
11           updating one or more fields in the new node that correspond to the one or  
12      more fields in the existing node; and  
13           performing a single atomic operation that modifies the next pointer of the  
14      existing node to point to the new node and also marks the next pointer to indicate  
15      that the existing node is deleted, wherein the existing node remains in the linked  
16      list after being marked as deleted, whereby the new node becomes part of the  
17      linked list and the existing node is deleted in a single atomic operation.
- 1           2.       (Original) The method of claim 1, wherein after the existing node  
2       has been deleted, the method further comprises splicing the existing node out of  
3       the linked list by atomically modifying the next pointer of a node immediately

4 preceding the existing node in the linked list to point to the new node, instead of  
5 pointing to the existing node.

1 3. (Original) The method of claim 2, wherein if a process that deleted  
2 the existing node does not perform the splicing operation, another process, which  
3 subsequently detects that the existing node has been deleted, performs the splicing  
4 operation.

1 4. (Original) The method of claim 1, wherein copying a snapshot of  
2 the existing node to the new node involves:  
3 copying the contents of the existing node to the new node;  
4 examining the next pointer of the existing node to determine if the existing  
5 node has been deleted; and  
6 if the existing node has been deleted, taking a remedial action.

1 5. (Original) The method of claim 4, wherein taking the remedial  
2 action involves:  
3 following the next pointer of the existing node in an attempt to find an  
4 updated version of the existing node; and  
5 if an updated version of the existing node is found, copying a snapshot of  
6 the updated version of the existing node to the new node.

1 6. (Original) The method of claim 1, further comprising deleting a  
2 target node from the linked list by:  
3 receiving a reference to the target node to be deleted from the linked list;  
4 atomically marking a next pointer in the target node to indicate that the  
5 target node is deleted; and

6           atomically modifying the next pointer of a node immediately preceding the  
7   target node in the linked list to point to a node immediately following the target  
8   node in the linked list, instead of pointing to the target node, thereby splicing the  
9   target node out of the linked list.

1           7.       (Original) The method of claim 6, wherein after the target node is  
2   spliced out of the linked list, the method further comprises modifying the next  
3   pointer of the target node so that the next pointer remains marked but points to a  
4   node immediately preceding the target node instead of the node immediately  
5   following node the target node in the linked list.

1           8.       (Original) The method of claim 1, further comprising inserting an  
2   additional node into the linked list by:  
3           identifying a node immediately preceding the additional node in the linked  
4   list;  
5           identifying a node immediately following the additional node in the linked  
6   list; and  
7           splicing the additional node into the linked list by,  
8                       setting the next pointer for the additional node to point to  
9                       the immediately following node, and  
10                      atomically updating the next pointer of the immediately  
11                      preceding node to point to the additional node.

1           9.       (Original) The method of claim 1, further comprising reading a  
2   snapshot of multiple fields from a target node in the linked list by:  
3           reading the multiple fields from the target node;  
4           examining the next pointer of the target node to determine if the target  
5   node has been deleted; and

6           if the target node has been deleted, taking a remedial action.

1           10.   (Original) The method of claim 9, wherein taking the remedial  
2   action involves:  
3           following the next pointer of the target node in an attempt to find an  
4   updated version of the target node; and  
5           if an updated version of the target node is found, repeating the process of  
6   reading a snapshot of the multiple fields from the updated version of the target  
7   node.

1           11.   (Original) The method of claim 1, wherein atomically modifying  
2   the next pointer of the existing node to indicate that the existing node is deleted  
3   involves setting a “deleted bit” in the next pointer.

1           12.   (Original) The method of claim 1, wherein while atomically  
2   modifying the next pointer of the existing node, if the next pointer indicates that  
3   the existing node is already deleted, the atomic modification operation fails and  
4   the method further comprises taking a remedial action to deal with the fact that the  
5   existing node is already deleted.

1           13.   (Original) The method of claim 1, wherein a given node in the  
2   linked list includes:  
3           a key that contains an identifier for the given node;  
4           one or more fields containing data values or pointers to data values  
5   associated with the given node; and  
6           a next pointer that contains the address of a node that immediately follows  
7   the given node in the linked list, and that also contains a deleted indicator, which  
8   indicates whether the given node has been deleted.

1           14.     (Original) The method of claim 1, further comprising periodically  
2 performing a garbage-collection operation to reclaim deleted nodes that have  
3 become unreachable.

1           15.     (Currently amended) A computer-readable storage medium storing  
2 instructions that when executed by a computer cause the computer to perform a  
3 method for performing a lock-free update to one or more fields in an existing node  
4 in a linked list, the method comprising:  
5           receiving a reference to the existing node in the linked list, wherein the  
6 existing node contains the one or more fields to be updated;  
7           obtaining a new node to be added to the linked list, wherein other  
8 processes do not possess references to the new node and therefore cannot initially  
9 access the new node;  
10          copying a snapshot of the existing node to the new node, which includes  
11 copying a next pointer of the existing node to the new node so that the new node  
12 points to a node immediately following the existing node;  
13          updating one or more fields in the new node that correspond to the one or  
14 more fields in the existing node; and  
15          performing a single atomic operation that modifies a next pointer of the  
16 existing node to point to the new node and also marks the next pointer to indicate  
17 that the existing node is deleted, wherein the existing node remains in the linked  
18 list after being marked as deleted, whereby the new node becomes part of the  
19 linked list and the existing node is deleted in a single atomic operation.

1           16.     (Original) The computer-readable storage medium of claim 15,  
2 wherein after the existing node has been deleted, the method further comprises  
3 splicing the existing node out of the linked list by atomically modifying the next

4 pointer of a node immediately preceding the existing node in the linked list to  
5 point to the new node, instead of pointing to the existing node.

1 17. (Original) The computer-readable storage medium of claim 16,  
2 wherein if a process that deleted the existing node does not perform the splicing  
3 operation, another process, which subsequently detects that the existing node has  
4 been deleted, performs the splicing operation.

1 18. (Original) The computer-readable storage medium of claim 15,  
2 wherein copying the snapshot of the existing node to the new node involves:  
3 copying the contents of the existing node to the new node;  
4 examining the next pointer of the existing node to determine if the existing  
5 node has been deleted; and  
6 if the existing node has been deleted, taking a remedial action.

1 19. (Original) The computer-readable storage medium of claim 18,  
2 wherein taking the remedial action involves:  
3 following the next pointer of the existing node in an attempt to find an  
4 updated version of the existing node; and  
5 if an updated version of the existing node is found, copying a snapshot of  
6 the updated version of the existing node to the new node.

1 20. (Original) The computer-readable storage medium of claim 15,  
2 wherein the method further comprises deleting a target node from the linked list  
3 by:  
4 receiving a reference to the target node to be deleted from the linked list;  
5 atomically marking a next pointer in the target node to indicate that the  
6 target node is deleted; and

7           atomically modifying the next pointer of a node immediately preceding the  
8   target node in the linked list to point to a node immediately following the target  
9   node in the linked list, instead of pointing to the target node, thereby splicing the  
10   target node out of the linked list.

1           21.   (Original) The computer-readable storage medium of claim 20,  
2   wherein after the target node is spliced out of the linked list, the method further  
3   comprises modifying the next pointer of the target node so that the next pointer  
4   remains marked but points to a node immediately preceding the target node  
5   instead of the node immediately following node the target node in the linked list.

1           22.   (Original) The computer-readable storage medium of claim 15,  
2   wherein the method further comprises inserting an additional node into the linked  
3   list by:  
4           identifying a node immediately preceding the additional node in the linked  
5   list;  
6           identifying a node immediately following the additional node in the linked  
7   list; and  
8           splicing the additional node into the linked list by,  
9                    setting the next pointer for the additional node to point to  
10                   the immediately following node, and  
11                   atomically updating the next pointer of the immediately  
12                   preceding node to point to the additional node.

1           23.   (Original) The computer-readable storage medium of claim 15,  
2   wherein the method further comprises reading a snapshot of multiple fields from a  
3   target node in the linked list by:  
4           reading the multiple fields from the target node;

5           examining the next pointer of the target node to determine if the target  
6   node has been deleted; and  
7           if the target node has been deleted, taking a remedial action.

1           24.   (Original) The computer-readable storage medium of claim 23,  
2   wherein taking the remedial action involves:  
3           following the next pointer of the target node in an attempt to find an  
4   updated version of the target node; and  
5           if an updated version of the target node is found, repeating the process of  
6   reading a snapshot of the multiple fields from the updated version of the target  
7   node.

1           25.   (Original) The computer-readable storage medium of claim 15,  
2   wherein atomically modifying the next pointer of the existing node to indicate that  
3   the existing node is deleted involves setting a “deleted bit” in the next pointer.

1           26.   (Original) The computer-readable storage medium of claim 15,  
2   wherein while atomically modifying the next pointer of the existing node, if the  
3   next pointer indicates that the existing node is already deleted, the atomic  
4   modification operation fails and the method further comprises taking a remedial  
5   action to deal with the fact that the existing node is already deleted.

1           27.   (Original) The computer-readable storage medium of claim 15,  
2   wherein a given node in the linked list includes:  
3           a key that contains an identifier for the given node;  
4           one or more fields containing data values or pointers to data values  
5   associated with the given node; and



1 a next pointer that contains the address of a node that immediately follows  
2 the given node in the linked list, and that also contains a deleted indicator, which  
3 indicates whether the given node has been deleted.

1 28. (Original) The computer-readable storage medium of claim 15,  
2 wherein the method further comprises periodically performing a garbage-  
3 collection operation to reclaim deleted nodes that have become unreachable.

1 29. (Currently amended) An apparatus that performs a lock-free update  
2 to one or more fields in an existing node in a linked list, comprising:  
3 a node obtaining mechanism configured to obtain a new node to be added  
4 to the linked list, wherein other processes do not possess references to the new  
5 node and therefore cannot initially access the new node;  
6 a copying mechanism configured to copy a snapshot of the existing node  
7 to the new node, which includes copying a next pointer of the existing node to the  
8 new node so that the new node points to a node immediately following the  
9 existing node;  
10 an updating mechanism configured to update one or more fields in the new  
11 node that correspond to the one or more fields in the existing node; and  
12 a modification mechanism configured to perform a single atomic operation  
13 that modifies a next pointer of the existing node to point to the new node and also  
14 marks the next pointer to indicate that the existing node is deleted, wherein the  
15 existing node remains in the linked list after being marked as deleted, whereby the  
16 new node becomes part of the linked list and the existing node is deleted in a  
17 single atomic operation.

1 30. (Original) The apparatus of claim 29, further comprising a splicing  
2 mechanism, wherein after the existing node has been deleted, the splicing

3 mechanism is configured to splice the existing node out of the linked list by  
4 atomically modifying the next pointer of a node immediately preceding the  
5 existing node in the linked list to point to the new node, instead of pointing to the  
6 existing node.

1 31. (Original) The apparatus of claim 30, wherein if a process that  
2 deleted the existing node does not activate the splicing mechanism, another  
3 process, which subsequently detects that the existing node has been deleted,  
4 activates the splicing mechanism.

1 32. (Original) The apparatus of claim 29, wherein the copying  
2 mechanism is configured to:  
3 copy the contents of the existing node to the new node;  
4 examine the next pointer of the existing node to determine if the existing  
5 node has been deleted; and  
6 if the existing node has been deleted, to take a remedial action.

1 33. (Original) The apparatus of claim 32, wherein while taking the  
2 remedial action, the copying mechanism is configured to:  
3 follow the next pointer of the existing node in an attempt to find an  
4 updated version of the existing node; and  
5 if an updated version of the existing node is found, to copy a snapshot of  
6 the updated version of the existing node to the new node.

1 34. (Original) The apparatus of claim 29, further comprising a deletion  
2 mechanism configured to delete a target node from the linked list, wherein the  
3 deletion mechanism is configured to:  
4 receive a reference to the target node to be deleted from the linked list;

5           atomically mark a next pointer in the target node to indicate that the target  
6 node is deleted; and to  
7           atomically modify the next pointer of a node immediately preceding the  
8 target node in the linked list to point to a node immediately following the target  
9 node in the linked list, instead of pointing to the target node, thereby splicing the  
10 target node out of the linked list.

1           35.   (Original) The apparatus of claim 34, wherein after the target node  
2 is spliced out of the linked list, the deletion mechanism is configured to modify  
3 the next pointer of the target node so that the next pointer remains marked but  
4 points to a node immediately preceding the target node instead of the node  
5 immediately following node the target node in the linked list.

1           36.   (Original) The apparatus of claim 29, further comprising an  
2 insertion mechanism configured to insert an additional node into the linked list,  
3 wherein the insertion mechanism is configured to:  
4           identify a node immediately preceding the additional node in the linked  
5 list;  
6           identify a node immediately following the additional node in the linked  
7 list; and to  
8           splice the additional node into the linked list by,  
9                   setting the next pointer for the additional node to point to  
10                  the immediately following node, and  
11                  atomically updating the next pointer of the immediately  
12                  preceding node to point to the additional node.

1           37.     (Original) The apparatus of claim 29, further comprising a reading  
2 mechanism configured to read a snapshot of multiple fields from a target node in  
3 the linked list, wherein the reading mechanism is configured to:  
4           read the multiple fields from the target node;  
5           examine the next pointer of the target node to determine if the target node  
6 has been deleted; and  
7           if the target node has been deleted, to take a remedial action.

1           38.     (Original) The apparatus of claim 37, wherein while taking the  
2 remedial action, the reading mechanism is configured to:  
3           follow the next pointer of the target node in an attempt to find an updated  
4 version of the target node; and  
5           if an updated version of the target node is found, to repeat the process of  
6 reading a snapshot of the multiple fields from the updated version of the target  
7 node.

1           39.     (Original) The apparatus of claim 29, wherein while atomically  
2 modifying the next pointer of the existing node to indicate that the existing node  
3 is deleted, the modification mechanism is configured to set a “deleted bit” in the  
4 next pointer.

1           40.     (Original) The apparatus of claim 29, wherein while atomically  
2 modifying the next pointer of the existing node, if the next pointer indicates that  
3 the existing node is already deleted, the modification mechanism is configured to:  
4           fail the modification operation fails; and to  
5           take a remedial action to deal with the fact that the existing node is already  
6 deleted.

1           41.    (Original) The apparatus of claim 29, wherein a given node in the  
2 linked list includes:  
3           a key that contains an identifier for the given node;  
4           one or more fields containing data values or pointers to data values  
5 associated with the given node; and  
6           a next pointer that contains the address of a node that immediately follows  
7 the given node in the linked list, and that also contains a deleted indicator, which  
8 indicates whether the given node has been deleted.

1           42.    (Original) The apparatus of claim 29, further comprising a garbage  
2 collection mechanism configured to periodically perform a garbage-collection  
3 operation to reclaim deleted nodes that have become unreachable.